



INTERCONNECT

NOW FEATURING **SMARTKEY**

INTERCONNECT

A SMART SOLUTION FOR MULTIFAMILY HOUSING

- Meets fire code rating for emergency panic exit
- ANSI/BHMA Graded
- Meets 3 hour UL rating
- Meets 4.12.9 ADA requirements on all lever options
- 100% all metal components
- Fits standard door prep - 5 1/2" center to center
- Easy installation
- New SmartKey™ Cylinder - Re-Key in Seconds



Kwikset
The Beauty of Strength.

A SMART SOLUTION FOR MULTIFAMILY HOUSING

INCREASE EFFICIENCY

SAVE TIME & MONEY






ADD SECURITY WITH KEY CONTROL

Interconnect

Specifications:

Door Prep	Crossbore 2-1/8" Edge Bore 1" 5-1/2" center-to-center only.
Backset	Complete locksets: 2-3/4" UL or 2-3/8" UL must specify Interior assemblies: Determined by handleset ordered.
Door Thickness	1-3/4" and 2-1/4".
Cylinder	506, 508 - utilize 6-pin on 780 deadbolt. 505, 507 - utilize 5-pin on 660 deadbolt. 502, 499, 503 - determined by handleset ordered. SmartKey or Pin & Tumbler, All SmartKey utilizes 5 pin keys
Faceplates	Complete locksets: No default - must specify faceplate. 1" round corner, 1" square corner, 1-1/8 WFL square. Interior assemblies: determined by handleset ordered.
Strikes	Complete locksets: UL 3028, 3031, (WFL option 3846) Deadbolt Strike: UL 5278, 3223 (WFL 4632 opt.) Interior assemblies: determined by handleset ordered.
Door Handing	506, 508, 505, 507 - reversible 502,499,503 - specify handling.
ANSI/BHMA	506, 508, 503, 507 - Grade 2 505, 507 - Grade 3 502 - Determined by handleset ordered. 499 not applicable.
ADA	All lever options meet 4.12.9 ADA requirements.
UL	Meets 3 hour fire rating for all functions.

Functions:

	Deadlocking Latch: Operated by grip either side except when locked by key outside and thumbturn inside. Deadbolt operated by key outside and thumbturn inside. Inside grip simultaneously retracts deadlatch and deadbolt latch. -506UL/505UL <small>F96</small>
	Plain Latch: operated by grip either side. Deadbolt operated by key outside and thumbturn inside. Inside grip simultaneously retracts plain latch and deadbolt latch. -508UL/507UL <small>F95</small>
	Interior Assembly Only: Grip inside simultaneously retracts plain latch and deadbolt latch when matched with handleset. on outside. -503 Interior
	Interior Assembly Only: Grip inside simultaneously retracts plain latch and deadbolt latch when matched with handleset on outside. -502 Interior
	Interior Assembly Only: Inside grip acts as a pull only. Non-operable for inactive leaf of double doors when matched to dummy Handleset on outside. -499 Interior

Note: ANSI/BHMA functions are listed in italics.

SMARTKEY featuring BumpGuard™:

RE-KEY IN THREE EASY STEPS



1
Insert functioning key and turn 1/4 turn clockwise.

2
Insert and remove the SmartKey learn tool. Remove functioning key.


3
Insert new key and turn 1/2 turn counter-clockwise. Your lock is now re-keyed!

Finishes:



LO3/3 Polished Brass 5 Antique Brass 11P Venetian Bronze 15 Satin Nickel 15A Antique Nickel 26 Polished Chrome 26D Satin Chrome

Dimensions:



Design	A	B	C	D	E
Interconnect	1 27/64"	2 15/32"	5 3/8"	2 53/64"	9 63/64"

Kwikset
The Beauty of Strength.®